

Agilent 990 Micro GC J&W CP-Sil 19 CB Channels

Introduction

The Agilent 990 Micro GC system has been designed to accommodate up to four analytical channels. Each channel holds its own MEMS-based inlet, isothermal column, and micro TCD detector.

These channels are available in > 15 different column chemistries and > 60 unique configurations. Agilent offers different lengths in straight or backflush (BF) configurations. Backflush allows heavier compounds to be backflushed, leaving a clean column and enabling faster analysis. Backflush to detector (BF2D) backflushes to the detector instead of the vent, using pretuned restrictions. This results in a composite peak for the backflushed compounds, typically C6+.

Agilent J&W CP-Sil 19 CB channels have a medium polarity and are highly selective for resolving the natural gas odorizing agent tetrahydrothiophene from the typical natural gas matrix components at very low concentrations.

Table 1. Available J&W CP-Sil 19 CB channels for the Agilent 990 Micro GC.

Part Number	Description	Length (m)	Precolumn (m)	BF
G3588-63764	MGC 19CB, 6 m, HI, Str, FactI	6	–	No
G3588-63768	MGC 19CB THT, 6 m, HI, Str, FactI	6	–	No
G3588-63789	MBC 19CB, 12 m, HI, BF 1 m, FactI	12	1	Yes

Product features

Configuration

- J&W CP-Sil 19 CB phase
- J&W CP-Sil 19 CB Backflush column (optional)

Control

- Independent control of the channel
- Pneumatics, including proportional column pressure programming
- Independent column, injector, and detector settings

Injector

- Micromachined injector with no moving parts
- Injection volume of 1 to 10 μL , software-selectable injection time
- Heated injector, up to 110 $^{\circ}\text{C}$, including heated sample transfer line

Column¹

- Temperature range: up to 180 $^{\circ}\text{C}$, isothermal
- Resolution: see Table 2

Detector

- Micromachined thermal conductivity detector (TCD)
- Dual-channel TCD (sample/reference flow)
- Internal volume: 200 nL per channel
- Four filaments

Detection limit, TCD^{1,4}

- See Table 2

Operating range, TCD

- Linear dynamic range²: 10^5

Repeatability¹

- See Table 2

Carrier gas³

- He, H₂, N₂, or Ar, 550 $\pm$ 10 kPa (80 $\pm$ 1.5 psi) input

Sampling

- Sample inlet: 1.6 mm (1/16 in) stainless steel (SST) Valco fitting, with replaceable 5 μm SST filter
- Sample conditions: noncondensing gas of 0 to 110 $^{\circ}\text{C}$
- Maximum sample inlet pressure: 100 kPa (14.5 psi)

Environmental conditions

- Ambient operating temperature: 0 to 50 $^{\circ}\text{C}$
- Ambient operating humidity: 5 to 95% RH (noncondensing)
- Storage extremes: –40 to 70 $^{\circ}\text{C}$
- Altitude: up to 2,000 m above sea level

¹ Specifications are determined under specific test conditions for this channel and are valid for new channels only. Results may vary with different conditions used and may degrade with use.

² For full range calibrations (low ppm to 100%), multilevel calibration is strongly advised.

³ Hydrogen carrier is not permitted on the Agilent 990 Mobile Micro GC system.

⁴ All specifications are determined with He carrier.

Table 2. Specifications for all available J&W CP-Sil 19 CB channels for the Agilent 990 Micro GC.^{1,4}

Part Number	Description	Length (m)	Precolumn (m)	BF	Resolution (iC4/nC4 at 0.15/0.2%)	Detection Limit (As TBM)	Repeatability (Peak Area at 0.15/0.2%)
G3588-63764	MGC 19CB, 6 m, HI, Str, FactI	6	–	No	1.5	0.3 ppm	< 0.5% RSD
G3588-63768*	MGC 19CB THT, 6 m, HI, Str, FactI	6	–	No	1.3*	0.6 ppm*	< 10% RSD*
G3588-63789	MBC 19CB, 12 m, HI, BF 1 m, FactI	12	1	Yes	2.5	0.6 ppm	< 0.5% RSD

*Channel specifically tuned for THT. Resolution and precision measured as THT/n-C₄ at 4.5 ppm each. Detection limit measured using THT at 4.5 ppm.

www.agilent.com

This information is subject to change without notice.

© Agilent Technologies, Inc. 2024
Printed in the USA, July 24, 2024
5994-7605EN